

STANLESS STEEL FLEXIBLE CONDUIT

jacketed – Squarelocked Flexible Metal Conduit



Part No.	NORMAL SIZE		I.D. (MM)	O.D. (MM)	BEND RADIUS (MM)	PACKING (M / Coil)
	(IN.)	(MM) LARGEST RECTUM				
SPSSB006	3/16"	Φ6	6.0	9.2	55	100
SPSSB007	1/4"	Φ8	8.0	11.0	55	100
SPSSB008	5/16"	Φ10	10.0	13.0	60	50
SPSSB010	3/8"	Φ12	12.5	16.6	60	50
SPSSB011	1/2"	Φ15	16.1	20.5	85	50
SPSSB012	3/4"	Φ20	20.8	25.5	100	50
SPSSB013	1"	Φ25	26.4	31.6	120	50
SPSSB014	1-1/4"	Φ32	34.5	39.6	150	25
SPSSB015	1-1/2"	Φ38	40.0	46.8	180	25
SPSSB016	2"	Φ51	51.0	58.6	220	20
SPSSB017	2-1/2"	Φ64	63.0	73.5	310	10
SPSSB018	3"	Φ75	76.5	85.5	350	10
SPSSB019	4"	Φ100	102.0	112.5	410	5

Remarks: 1. The color of the PVC is black. If order the grey one, the Part No. is SPSSG
2. The tolerance is ±0.5mm.

ITEM	SPSSB
MATERIAL	STAINLESS STEEL +PVC
IP RATING	IP65
WORKING TEMPERATURES	-20°C ~ 90°C
COMPRESSION STRENGTH	2400N ¹
PULL OFF STRENGTH OF CONDUIT	1700N ²