

Fiberglass Reinforced Polyester Enclosures IP65

TIBOX
AUSTRALIA
TOTAL ENCLOSURE SOLUTIONS



Material: Fibre glass/ Polyester,
self-extinguishable

Colour:RAL7035

Protection degree:IP65

Working temperature:-40°C to +120°C

Mechanical impact:IK08

Enclosure includes:

Door with lock system, enclosure, wall mount brackets 4pcs/set.

Mounting plate to be supplied separately as per the clients request.

Resistance against rusting and corrosion by chemicals or atmospheric conditions. Ideal for marine, coastal and waste water applications.

Door hinges allows more than 180° opening.

Model	Size HxWxD mm.	Polyester Enclosure	
		ความหนา	ระดับป้องกัน
TIP-325	300x250x140	1.5	IP65 IK08
TIP-430	400x300x200	1.5	IP65 IK08
TIP-440	400x400x200	1.5	IP65 IK08
TIP-540	500x400x200	1.5	IP65 IK08
TIP-640	600x400x230	1.5	IP65 IK08
TIP-650	600x500x230	1.5	IP65 IK08
TIP-860	800x600x300	1.5	IP65 IK08

1. Wall Mount Brackets TYP01

2. Standard Lock :



Standard lock
model: MS-01
package: 1pc



Key lock
model: MS705-3E
package: 1pc



Wall mount brackets
model: TYP-01 package: 4pcs/set