

Plug and Sockets

IP 67

EN60309-1,-2 DIN VDE 0620-1
IEC 60884-1

Material : Polyamide 6, UL94 V0
Halogen free, IK08

Test of resistance to glow wire 960 C
Temp : -40 - 125 C



200-250 V, 50/60 Hz single phase	16 A	2P+E	02821	02801	02701	02601	02621
		3P+E	02822	02802	02702	02602	02622
		3P+N+E	02823	02803	02703	02603	-
	32 A	2P+E	02824	02804	02704	02604	02624
		3P+E	02825	02805	02705	02605	02625
		3P+N+E	02826	02806	02706	02606	-
	63 A	2P+E	02871	02851	02751	02651	02671
		3P+E	02872	02852	02752	02652	02672
		3P+N+E	03873	03853	02753	02653	02673
	125 A	2P+E	02874	02854	02754	02654	02674
		3P+E	02875	02855	02755	02655	02675
		3P+N+E	-	-	-	-	-
380-415 V, 50/60 Hz three phase	16 A	3P+E	03822	03802	03702	03602	03622
		3P+N+E	03823	03803	03703	03603	03623
	32 A	3P+E	03825	03805	03705	03605	03625
		3P+N+E	03826	03806	03706	03606	03626
	63 A	3P+E	03872	03852	03752	03652	03672
		3P+N+E	03873	03853	03753	03653	03673
	125 A	3P+E	03875	03855	03755	03655	03675
		3P+N+E	03876	03856	03756	03656	03676

