

Plug and Sockets

IP 44

EN60309-1,-2 DIN VDE 0620-1
IEC 60884-1

Material : Polyamide 6, UL94 V0

Halogen free , IK08

Test of resistance to glow wire 960 C

Temp : -40 - 125 C



200-250 V,
50/60 Hz
single phase

16 A 2P+E

00102

00104

00110

00120

00130

IP 44

EN60309-1,-2 DIN VDE 0620-1
IEC 60884-1

Material : Polyamide 6, UL94 V0

Halogen free , IK08

Test of resistance to glow wire 960 C

Temp : -40 - 125 C



200-250 V,
50/60 Hz
single phase

2P+E

02321

02301

02201

02101

02121

16 A

3P+E

02322

02302

02202

02102

02122

3P+N+E

02323

02303

02203

02103

02123

2P+E

02324

02304

02204

02104

02124

32 A

3P+E

02325

02305

02205

02105

02125

3P+N+E

02326

02306

02206

02106

03126

380-415 V,
50/60 Hz
three phase

16 A

3P+E

03322

03302

03202

03102

03122

3P+N+E

03323

03303

03203

03103

03123

32 A

3P+E

03325

03305

03205

03105

03125

3P+N+E

03326

03306

03206

03106

03126

