


# PA 6 Flexible Conduit



We can supply UL94-V2, UL94-V0  
Flame retardant Conduits

- Material: Polyamide 6
- Temperature Range: Min-40°C, Max 115°C, Short-term 150°C
- Properties: flexible and excellent tenacity, medium wall thickness, glossy surface, wind resistant, high mechanical strength, resistant to oil, acid and solvents. anti-friction black tubings are UV-resistant, free of halogen, phosphor and cadmium
- Applications: Machine tool, machine building, electric control system etc.

**CE**  
**ROHS PAHS**

Article No. (B) , (G)	ID×OD mm×mm	Stat.r mm	Dyn.r mm	PU m/ring
SS-PAAD10.0(B. G)	7.0×10.0	13	35	100
SS-PAAD13.0(B. G)	10.0×13.0	20	45	100
SS-PAAD15.8(B. G)	12.0×15.8	35	55	100
SS-PAAD18.5(B. G)	14.3×18.5	40	65	50
SS-PAAD20.0(B. G)	16.0×20.0	45	75	50
SS-PAAD21.2(B. G)	17.0×21.2	45	75	50
SS-PAAD25.0(B. G)	21.0×25.0	50	85	50
SS-PAAD28.5(B. G)	23.0×28.5	55	100	50
SS-PAAD34.5(B. G)	29.0×34.5	65	120	25
SS-PAAD42.5(B. G)	36.0×42.5	90	150	25
SS-PAAD54.5(B. G)	48.0×54.5	100	190	25
SS-PAAD67.2(B. G)	56.3×67.2	130	270	20
SS-PAAD80.0(B. G)	66.5×80.0	170	310	20

